DIALOG(R)File 351:Derwent WPI (c) 2001 Derwent Info Ltd. All rts. reserv.

011338750

WPI Acc No: 1997-316655/199729

XRAM Acc No: C97-102218 XRPX Acc No: N97-262144

Microporous film used for microfiltration of gas or liquid -

comprising polyolefin and double layered particles of core particles of

elastomer

Patent Assignee: TOKUYAMA SODA KK (TOKU ) Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week

JP 9124814 A 19970513 JP 95287603 A 19951106 199729 B

Priority Applications (No Type Date): JP 95287603 A 19951106 Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes JP 9124814 A E 6 CO8J-009/00

Abstract (Basic): JP 9124814 A

A microporous film comprises 90-40 weight % a polyolefin and 10-60 weight % of double layered particles which have an average diaphragm of 0.01-10 microns and comprise core particles of an elastomer and the surface layer of the core of open cells having a maximal pore diaphragm of up to 7 microns and the void ratio of 10-70 weight % and is drawn to give molecular orientation.

USE - The microporous film is used for microfiltration of gas or liquid, as a separator in battery dehumidifier, de-oxygeniser and as diapers, bed sheet, waterproofing sheet, etc.

ADVANTAGE - The film less contains inorganic particles, and has a satisfied impact strength and durability usable under hazard conditions for long time.

Dwg.0/0

Title Terms: MICROPOROUS; FILM; GAS; LIQUID; COMPRISE; POLYOLEFIN;

DOUBLE; LAYER; PARTICLE; CORE; PARTICLE; ELASTOMER

Derwent Class: A17; A18; A85; A88; A96; J01; L03; X16

International Patent Class (Main): C08J-009/00 International Patent Class (Additional): C08L-023-02

File Segment: CPI; EPI

6/5/22